




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B24C 7/00, 1/00		(11) International Publication Number: WO 99/22909
A1		(43) International Publication Date: 14 May 1999 (14.05.99)
(21) International Application Number: PCT/NL98/00613 (22) International Filing Date: 23 October 1998 (23.10.98) (30) Priority Data: 1007421 3 November 1997 (03.11.97) NL (71)(72) Applicant and Inventor: KONINGS, Huibert [NL/NL]; Brahmstraat 55, NL-1447 RT Purmerend (NL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: METERING DEVICE FOR CRYOGENIC PELLETS



(57) Abstract

The invention concerns a metering device (1) for cryogenic pellets which are used in a blast cleaning apparatus to treat surfaces. The cryogenic pellets are by example bars of compressed dry ice (carbon dioxide). The metering device (1) is characterised by the use of sliding surfaces which are treated with a layer of nickel which contains ceramic material or sapphire powder. The metering device (1) has a metering disk (4) with openings (5) which while turning pass the intake opening (2) and thereafter pass the exhaust (3) opening where the pellets are transported to the mixing unit (25). The metering disk (4) is confined between plates (7, 8) where inbetween an elastic seal (15-17) is placed. The plates (7, 8) are pressed against the metering disk (4) with sets of springs. The metering device (1) has no ventilation openings for the openings (5) in the disk (4) and the space around the disk is not ventilated. The metering disk (4) has only one axis (6) with a bearing (10).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

-1-

Metering device for cryogenic pellets.

The invention concerns a metering device for cryogenic pellets which are used in a blast cleaning apparatus for treatment of surfaces. The cryogenic pellets are by example bars of compressed dry ice (carbon dioxide).

Metering devices are known from the publication NL-A-9301237. It is found that this device does not function well because the metering device constantly freezes because the metering disk is not sufficiently isolated from the outside air. It is found that the metering disk needs a special surface treatment as lubricating is practical impossible as the operating temperature is about minus 80 degrees Celsius.

The invention will neutralise these disadvantages by providing the sliding surfaces with a layer of nickel containing very fine ceramic particles, like sapphire with a particle dimension of about 6 micron. Besides the metering disk is pressed between two plates which are elastic but gas-tight connected. The device is completely sealed except the intake and exhaust openings. Ventilation openings are entirely avoided.

The invention will be described with the drawings.

Fig. 1 shows a cross section over the metering device.

Fig. 2 shows the schema of the blast cleaning installation.

In the drawings is the isolation of conduits left out.

In Fig. 1 is with (1) the metering device indicated. At (2) is the supply of pellets, at (3) the exhaust. With (4) is indicated the metering disk. Metering disk (4) is preferably provided with 8 round holes (5) and is driven by shaft (6). Metering disk (4) rotates between plates (7, 8) where plate (7) carries the supply of pellets (2) and the supply of transport gas (9). Plate (8) carries the bearing with bearing ring (10), synthetic ring (11), securing ring

-2-

(12) and bearing surface (13). Seal (14) seals shaft against humidity. Synthetic ring (11) fastens bearing ring (10) in such a way that small oscillations of shaft (6) are absorbed, where at the same time the bearing construction
05 is sealed against penetration of humidity. Between plates (7) and (8) is a metallic seal, put together from ring (15) and ring (16) where between is mounted a thin metal bellows (17) and it is preferred that the connection is made by welding. metering disk (4) has only one shaft end (6).

10

At (18) is one of more tightening bolts which press plates (7) and (8) against metering disk (4) with disk springs. The surface (19) of metering disk (4) and plates (7) and (8) is treated with a layer of nickel which is filled with
15 powdered sapphire with a particle dimension of about 6 micron or any other feasible ceramic material. This layer has a low coefficient of friction and can be used as sliding surface without lubricating. The bearing surface (13) and the inside surface of bearing ring (10) are
20 treated the same way.

Plate (7) and (8) are reduced in thickness and at (20) is machined a recess to prevent irregular wear.

Fig. 2 shows the design of an installation. (21) is the storage chamber, (22) the supply of compressed gas, at (23)
25 are valves and at (24) a reducing valve for transportation gas. (25) is the mixing part and (26) the blasting nozzle.

The blast cleaning installation works as follows: with shaft (6) metering disk (4) is rotated with a (not drawn)
30 variable speed motor. From storage chamber (21) pellets fall via supply (2) in opening (5). When opening (5) arrives before exhaust (3) the pellets are blown by the transportation gas into exhaust (3). The pellets are then going via mixing part (25) with compressed gas to blow
35 nozzle (26).

It is important for a reliable operation that metering disk (4) is shut off from the outside air. The space (27)

-3-

between metering disk (4) and seal (15, 16 and 17) is not ventilated. Remaining gas, resting behind in opening (5) after the blowing off of the pellets is not expelled. In the case that sublimation of for example carbon dioxide in
05 the metering device (1) causes high pressure plates (7) and (8) will part and the gas will be released via supply (2) or exhaust (3) and provoke no damage.

Claims.

05 Metering device for cryogenic pellets for treatment of
surfaces which is provided with a metering disk (4) with
circular openings (5) where the cryogenic particles are
carried with compressed gas to a mixing part (25)
10 characterised by that metering disk (4) rotates between two
flat plates (7, 8) which are tightened with springs, where
plate (7) is provided with the supply opening (2) and the
transport gas opening (9) and in plate (8) the shaft
bearing (10, 11, 12 and 13) and the exhaust opening (3),
while the plates (7, 8) are bound together with sealing
ring (15, 16) which is provided with an elastic metal
bellows (17).

15 2. Metering device as in claim 1 characterised by that all
sliding surfaces of metering disk (4), plates (7, 8),
bearing surface (13) and bearing part (10) are treated with
a layer of nickel with ceramic particles or sapphire.

20 3. Metering device as in claim 1 and 2 characterised by
that the metering disk (4) contains 8 openings and only one
shaft (6).

25 4. Metering device as in claim 1, 2 and 3 characterised by
that bearing ring (10) for shaft (6) is secured with a
prestressed synthetic ring (11).

30 5. Metering device as in claim 1, 2, 3 and 4 characterised
by that openings (5) in metering disk and space (27) around
metering disk (4) are not ventilated.

* * * *

1/1

FIG 1





FIG 2



INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 98/00613

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B24C7/00 B24C1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B24C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 389 820 A (FONG CALVIN C ET AL) 28 June 1983 see column 6, line 5-17; figures 8,9 ---	1,2,5
A	US 4 617 064 A (MOORE DAVID E) 14 October 1986 see the whole document ---	1,3
A	NL 9 301 237 A (HARKO BV) 1 February 1995 cited in the application see the whole document ---	1
A	US 4 538 068 A (HANEY STEVEN J ET AL) 27 August 1985 see column 4, line 35 - column 5, line 23; figures 1,2 --- -/-	2



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

15 February 1999

Date of mailing of the international search report

22/02/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Petersson, M.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 98/00613

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 109 636 A (LLOYD DANIEL L ET AL) 5 May 1992 see the whole document ----	1
A	EP 0 268 449 A (MOORE DAVID EDWARD ;CRANE NEWELL DELL (US)) 25 May 1988 ----	
A	US 5 492 497 A (BROOKE ROBERT K ET AL) 20 February 1996 ----	
A	US 4 463 736 A (HAYWARD JR WALLACE) 7 August 1984 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 98/00613

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4389820 A	28-06-1983	NONE	
US 4617064 A	14-10-1986	AU 4728185 A EP 0191062 A WO 8600833 A	25-02-1986 20-08-1986 13-02-1986
NL 9301237 A	01-02-1995	NONE	
US 4538068 A	27-08-1985	NONE	
US 5109636 A	05-05-1992	US 4947592 A DE 68910826 D DE 68910826 T EP 0426749 A JP 4500931 T WO 9001396 A	14-08-1990 23-12-1993 16-06-1994 15-05-1991 20-02-1992 22-02-1990
EP 0268449 A	25-05-1988	US 4744181 A DK 397287 A GB 2197230 A JP 63127875 A NL 8701861 A	17-05-1988 18-05-1988 18-05-1988 31-05-1988 16-06-1988
US 5492497 A	20-02-1996	US 5415584 A AU 7730394 A WO 9508407 A	16-05-1995 10-04-1995 30-03-1995
US 4463736 A	07-08-1984	NONE	